


# PM

## CABLE MARKING

- Transparent holder for cable marking with Partex marking labels, tapes and tags of series PF, PL, PP or PFC.
- Four lengths, three widths and endless profiles cover most cable marking demands.
- Fitting and fastening with cable ties.
- Marking labels can be printed on-site using Partex software WinSign and various marking equipment.
- The label is easily inserted into the holder providing fast installation and protection of the marking.



### GENERAL INFORMATION

#### Design

Holder for marker tags with punched holes for mounting with cable ties. Two standard lengths in two sizes 9 mm respectively 12 mm widths. Suitable marker labels and tags are PF on a A4 size sheet and tags on PFC X-cards in credit card formats. Also ProMark PP-profile tags and PL tapes can be used. The labels or tags are easily pushed into the holder and will be protected from dust, oil etc.

#### Material

Cadmium and silicon free soft PVC according to special Partex formula.

#### Colour

Transparent.

#### Ink with transparent sleeves

Today we have several ways to write information onto different sleeves. One way is to write with ink on a marker tag which is then mounted in a sleeve with a pocket. When using ink it is very important that you only use ink, tags and sleeves from Partex

You may get a poor readability after a while if you combine ink, tags or sleeves from other suppliers with a Partex product. This is something Partex can't be responsible for.

#### Temperature range


Shape permanence from  $-30^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$  ( $-22^{\circ}\text{F}$  to  $+140^{\circ}\text{F}$ ).

#### Resistance

The product is tested according to Partex Product Test Program by the Swedish Test and Research Institute and has the following test properties:

- Flammability UL94-V0 @ 3mm.
- Resistant to UV radiation, corresponding to 1 year outdoors in the south of Sweden.
- Resistance to chemicals meets Partex Product Test Program.
- Resistance to temperature and ageing meets norms of Partex Product Test Program.

For application in hostile environments, please contact Partex for information.



**DIMENSIONS IN MM (NOMINAL)**

Type	Profile/Sleeve				Suitable marking label							
	Length	Width	Thickness	Width of hole	PF-10	PF-20	PP-046	PP-090	MK9-PL090	MK9-PL120	PFC042	PFC09518
PM-10033AN	33 mm	6 mm	1.5 mm	3 mm	YES	-	YES	-	-	-	YES	-
PM-20033AN	33 mm	11.3 mm	2.2 mm	3 mm	-	YES	-	YES	YES	-	-	-
PM-24033AN	33 mm	13.9 mm	2.5 mm	3.9 mm	-	YES	-	YES	YES	YES	-	YES
PM-20045AN	45 mm	11.3 mm	2.2 mm	3 mm	-	YES	-	YES	YES	-	-	-
PM-20066AN	66 mm	11.3 mm	2.2 mm	3 mm	-	YES	-	YES	YES	-	-	-
PM-24066AN	66 mm	13.9 mm	2.5 mm	3.9 mm	-	YES	-	YES	YES	YES	-	YES
PM-24094	94 mm	13.9 mm	2.5 mm	3.9 mm	-	YES	-	YES	YES	YES	-	-
PM-20KNT	20 m	11.3 mm	2.2 mm	-	-	YES	-	YES	YES	-	-	-
PM-20QKNT	20 m	11.3 mm	2.2 mm	3 mm	-	YES	-	YES	YES	-	-	-
PM-24KNT	20 m	13.9 mm	2.5 mm	-	-	YES	-	YES	YES	YES	-	YES
PM-24QKNT	20 m	13.9 mm	2.5 mm	3.9 mm	-	YES	-	YES	YES	YES	-	YES
PM-20BNT	100 m	11.3 mm	2.2 mm	-	-	YES	-	YES	YES	-	-	-
PM-24BNT	100 m	13.9 mm	2.5 mm	-	-	YES	-	YES	YES	YES	-	YES

QKNT = Ready punched profile with 10mm's punch distance, 20 meter per carton.  
 KNT = Unpunched profile, 20 meter per carton.

AN = Cut marker holders in standard lengths.  
 BNT= Unpunched profile on reel.

**SIZES AND PACKAGING**

Type	Details	Qty/Pack
PM-10033AN	PM10/33 transparent holder 33MM cut loose in bag	100 pcs
PM-20033AN	PM20/33 transparent holder 33MM cut loose in bag	100 pcs
PM-24033AN	PM24/33 transparent holder 33MM cut loose in bag	100 pcs
PM-20045AN	PM20/45 transparent holder 45MM cut loose in bag	50 pcs
PM-20066AN	PM20/66 transparent holder 66MM cut loose in bag	50 pcs
PM-24066AN	PM24/66 transparent holder 66MM cut loose in bag	50 pcs
PM-24094	PM24/94 transparent holder 94MM cut loose in bag	50 pcs
PM-20KNT	PM20 profile transparent in carton	20 m
PM-20QKNT	PM20 profile punched transparent in carton	20 m
PM-24KNT	PM24 profile transparent in carton	20 m
PM-24QKNT	PM24 profile punched transparent in carton	20 m
PM-20SNT	PM20 profile transparent on compactdisc	5 m
PM-20BNT	PM20 profile transparent on reel	100 m
PM-24BNT	PM24 profile transparent on reel	100 m


**APPLICATION**



Continuous PM profiles in flat "pizza" cartons



PM-sleeve with a label from a PF-sheet



Punched PM-20 and PM-24 sleeves for cable tie mounting